


MAXIMA ULTRA 68 - EQUILIBRAGE RESSORT OMEGA FRC ATML U

RESSORT			EQUILIBRAGE DE LA LISSE									
W	DIAMETER	COLOR	MAXIMA ULTRA 68 + OMEGA FRC ATML U									
			ACCESSOIRES	L (mm)	4000	4500	5000	5500	6000	6500	7000	7500
W+W	Ø 7.5 + Ø 7.5	BLANC + BLANC	ATML	W+W	Y	Y	W+Y	W+Y	Y+Y	Y+P	Y+P	P+P
W+Y	Ø 7.5 + Ø 9.0	BLANC + JAUNE	ATML + KIT ATML LIGHT R/G 2W	Y	Y	W+Y	W+Y	Y+Y	Y+Y	Y+P	P+P	P+P
Y	Ø 9.0	JAUNE	ATML + PCA ATM	Y	W+Y	W+Y	W+Y	Y+Y	Y+Y	P+P	P+B	P+B
Y+Y	Ø 9.0 + Ø 9.0	JAUNE + JAUNE	ATML + KIT ATML LIGHT R/G 2W + PCA ATM	Y	W+Y	W+Y	Y+Y	Y+Y	Y+P	P+P	P+B	B+B
Y+P	Ø 9.0 + Ø 9.5	JAUNE + VIOLET	ATML + GA ATM (*)	Y	W+Y	W+Y	W+Y	Y+Y	Y+Y	P+P	P+B	P+B
P+P	Ø 9.5 + Ø 9.5	VIOLET + VIOLET	ATML + KIT ATML LIGHT R/G 2W + GA ATM (*)	Y	W+Y	W+Y	W+Y	Y+Y	Y+Y	P+P	P+B	P+B
P+B	Ø 9.5 + Ø 11.0	VIOLET + NOIR	ATML + PCA ATM + GA ATM (*)	Y	W+Y	W+Y	Y+Y	Y+Y	P+P	P+B	P+B	B+B
B+B	Ø 11.0 + Ø 11.0	NOIR + NOIR	ATML + KIT ATML LIGHT R/G 2W + PCA ATM + GA ATM (*)	Y	W+Y	W+Y	Y+Y	Y+Y	P+P	P+B	B+B	B+B
			ATML + RST ATM	Y	W+Y	W+Y	Y+Y	Y+Y	P+P	P+B	B+B	B+B
			ATML + RST ATM + KIT ATML LIGHT R/G 2W	Y	W+Y	W+Y	Y+Y	Y+Y	P+P	P+B	B+B	B+B
			ATML + RST ATM + GA ATM (*)	W+Y	W+Y	Y+Y	Y+Y	Y+Y	P+P	P+B	B+B	B+B
			ATML + RST ATM + KIT ATML LIGHT R/G 2W + GA ATM (*)	W+Y	W+Y	Y+Y	Y+Y	Y+Y	P+P	B+B	B+B	B+B



(*) GA ATM = EBB KIT ATML

ABAQUES LUX

LUX		mm								
a \ b	80	90	100	110	120	135	145	155	165	175
90						116	108	102	98	94
100						110	103	98	94	91
110					123	104	99	94	91	
120					111	99	94	91		
135				111	100	90°				
145				102	94					
155			104	95	90					
165			95	90						
175		95	88							
185	96	88								α°

LUX G - LUX GV		mm									
a \ b	95	115	135	155	175	195	215	235	255	275	295
95						128	115	107	102	97	94
115						119	108	102	97	93	90
135					130	111	102	97	93	89	
155					114	103	97	92	88		
175					104	96	91	87			
195					107	96	90°				
215					96	89					
235					96	88					
255	105	96	87								
275	96	85									
295	94										α°

F - Installation possible seulement avec patte de 110 mm.